

KODIAK PROFESSIONAL GENERATORS

The **KODIAK AVR SERIES** are ON-THE-JOB generators that have a proven track record for consistent **quality** and **reliability**. All models have large fuel tanks for longer running hours and perform quietly and efficiently. The rugged wheelkit is a standard accessory with the 5500 and 7000 series.




Powered by
HONDA
ENGINES

FEATURES & BENEFITS

- Honda® 4-stroke OHV Engine
- Oil Alert™
- Maintenance-free brushless design
- Large fuel tanks
- Large quiet mufflers
- Rubber-mounted engine
- Longer-wearing generator components
- Convenient non-fuse breakers
- Fuel Gauge Indicator included
- GFCI 120V receptacles
- Full frame protection
- Made in Japan

		KD3000VR	KD5500VR	KD7000VR	KD7000VRS
ALTERNATOR	Rated (Max) Output	2400W (3000W)	4800W (5000W)	6000W (7000W)	
	AC Output	120V		120V/240V	
	Rated (Max.) Amps	20.0A (23.3A)	40.0A/20.0A (45.8/22.9A)	50.0A/25.0A (56.7/28.3A)	
	DC Output/ Amps	12V/8.3A			
ENGINE	Generator Type	AVR			
	Engine Model	Honda GX160 OHV	Honda GX340 OHV	Honda GX390 OHV	
	HP	5.5HP	11.0HP	13.0HP	
	Displacement	163 CC	337 CC	389 CC	
	Run Time (Half Load)	12.1 Hours	8.5 Hours	7.6 Hoursw	
	Fuel Tank Capacity	(4.2GAL) 16L	(6.6GAL) 25L		
	Starting System	Recoil		Recoil/ Electric Start	Electric Start
FEATURES	Battery Tray	No			Yes
	Automatic Idle Control	No	Yes		
	Noise (dB)	70.0dBA	78.0dBA	79.0dBA	
	Receptacles	Tee-slot GFCI 120V			
	Gen. Outlet Receptacles	2 x A	2 x A & 1 x B & 1 x C		
	Dimensions (in)	23.6"x18.5"x19.7"	27.2"x22.8"x21.1"		
Dry Weight	102lbs	171lbs	179lbs	185lbs	

GENERATOR OUTLET RECEPTACLES



A) GFCI AC Receptacle
NEMA 5-20R
120V - 20A T-Slot



B) Twist Lock AC
NEMA L5-30R
120V - 30A



C) Twist Lock AC
NEMA L14-30R
120V/240V - 20A

WHEELKIT:

SBXWHEELKIT

Incl. with KD5500VR & KD7000VR(S)

- Full frame wheel kit standard for SXB-Series Generators
- Features 10" pneumatic wheels
- Rugged design and construction
- Adjustable axle significantly reduces the weight of equipment



Made In
JAPAN