# BEE

## **HOT WATER PRESSURE WASHER**

## **Belt Drive • Electric Powered • Electric Heated**

 Downstream Adjustable Chemical Injector:
 For low pressure soap and chemical injection.

 Belt Drive Motor and Pump Combination:

Maximizes the life of your pump. Protective cover is easily removed for service.

 Quick Connect Hose Connectors:

For easy on/off connections and tangle free hoses.

- Stainless Steel Hood: Durable rust resistant hood.
- Large Burner Temperature Dial:

Adjust water temperature with ease.

- Auto Start/Stop:
   Unit operation controlled with trigger gun.
- Compact Design: Ideal for storing in tight spaces.

 All Electric Design Advantages: No re-fueling, no venting, no smoke, no fumes or heat exhaust.



 Easy Access On/Off Toggle Switch: Includes indicator light.

- Four Quick Connect Nozzles: Colour coded nozzles included are 0°, 15°, 25°, and soap QC.
- 50' High Pressure Hose: Durable non-marking steel braided hose.
- Quality Gun and Lance Combination:
   Easy pull trigger with 48" lance.
- Hour Meter: Ideal for regular service scheduling maintenance.
- High Quality Triplex
   Plunger Pump:
   All Dynablast pressure
   washers include GP/Interpump
   pumps with solid ceramic
   plungers, thermal pump
   protector and limited 5 year
   warranty.
- Continuous Heat:
   High efficiency heat exchanger creates constant heat, even after extended use.

### **ALL ELECTRIC**

SPECIFICATIONS	ASSEMBLED IN CANADA	
MODEL	H4030BEE3C	H4030BEE3D
Operating Pressure (PSI):	3000	3000
Volume (GPM):	4.0	4.0
Engine (HP):	7.5	7.5
Available Voltage (3 Phase):	460	575
Amps:	98	80
KW:	72	72
Pump Speed:	1400	1400
Unit Dimensions (LxWxH):	34"x22"x31"	34"x22"x31"
Unit Weight:	500 lbs	500 lbs

Features and specifications subject to change without prior notice.





#### Other Features: •

- High Pressure Blow Off Valve: For added safety.
- Baldor Electric ODP Motor
- Low Water Shutdown
- 24 Volt Operating Controls
- Solid Steel Casters with Rubber Feet



www.dynablast.com

Distributed by: