# BEN/P

## HOT WATER PRESSURE WASHER

### **Belt Drive • Electric Powered • NG or LP Heated**

- **Downstream Chemical Injector:** For low pressure soap and chemical injection.
- Quick Connect Hose Connectors: For easy on/off connections and tangle free hoses.
- Heavy Duty Steel Frame: I2 gauge steel with powder coated finish.
- High Pressure Blow-Off Valve: For added safety.
- **24 Volt Electronic Ignition:** Automatically ignites the pilot flame when turned on.
- Belt Drive Motor and Pump Combination. Maximizes the life of your pump.
- Large Burner Temperature Dial: Adjust water temperature with ease.
- Separate Unloader: Diverts water pressure when trigger is not in use. Includes easily adjustable pressure control knob and brass fittings.
- Time Delay Shutdown: Automatically shuts down the motor when not in use.

SPECIFICATIONS



Draft Hood Included



- Quality Gun and Lance Combination: Easy pull trigger with 48" lance.
- 50' High Pressure Hose: Durable non-marking steel braided hose.
- Stainless Steel Coil Skin: Durable rust resistant skin. Schedule 80 heating coil and 345,000 BTU burner

## High Quality Triplex Plunger Pump:

All Dynablast pressure washers include GP/Interpump pumps with solid ceramic plungers, thermal pump protector and limited 5 year warranty.

#### Other Features:

- Easy Access On/Off Rotary Switch
- Baldor Electric ODP Motor
- Flow Switch For added safety
- Four Quick Connect Nozzles
- A Vent Rated



| SPECIFICATIONS               | ASSEMIDLED IN CANADA |             |                 |                 |
|------------------------------|----------------------|-------------|-----------------|-----------------|
| MODEL                        | H3620BEN/P           | H3823BEN/P  | H4030BEN/P      | H5030BEN/P      |
| Operating Pressure (PSI):    | 2000                 | 2300        | 3000            | 3000            |
| Volume (GPM):                | 3.6                  | 3.8         | 4.0             | 5.0             |
| Motor (HP):                  | 5.0                  | 6.0         | 7.5             | 10              |
| Available Voltage (1 Phase): | -                    | 230         | 230             | 230             |
| Available Voltage (3 Phase): | 208/230/460/575      | -           | 208/230/460/575 | 208/230/460/575 |
| Amps:                        | 14/13/7/5            | 30          | 32/22/22/11/8   | 42/30/28/14/11  |
| Pump Speed:                  | 1450                 | 1450        | 1450            | 1450            |
| BTU:                         | 345,000              | 345,000     | 345,000         | 345,000         |
| Time Delay Shutdown          | YES                  | YES         | YES             | YES             |
| Unit Dimensions (LxWxH)      | 47"x23'x41"          | 47"x23'x41" | 47"x23'x41"     | 47"x23'x41"     |
| Unit Weight                  | 530 lbs              | 535 lbs     | 540 lbs         | 560 lbs         |

ASSEMBLED IN CANADA

Features and specifications subject to change without prior notice.





Distributed by: