

CRBG SERIES

COLD WATER PRESSURE WASHER

Belt Drive • Gasoline Powered • Industrial Cart

- **Downstream Adjustable Chemical Injector:**

For low pressure soap and chemical injection.

- **Quick Connect Hose Connectors:**

For easy on/off connections and tangle free hoses.

- **Honda GX Gasoline Engine**

Includes re-coil start and low oil alert system.

- **Separate Unloader with Easy Start Valve:**

Diverts water pressure when trigger is not in use. Includes easily adjustable pressure control knob and all brass fittings.

- **13" Never-Go-Flat Tires:**

Ball bearing construction with a steel rim and hub assembly.

- **Clear Inlet Filter:**

Helps reduce contaminants from entering the pump.

- **Pressure Gauge**



Powered by
HONDA
ENGINES

- **Rubber Foot:**
Reduces vibration

- **Four Quick Connect Nozzles:**

Colour coded nozzles included are 0°, 15°, 25° and soap.

- **50' High Pressure Hose:**

Durable non-marking steel braided hose.

- **Heavy Duty Cart:**

With power coated finish.

- **Quality Gun and Stainless Steel Lance Combination:**

Easy pull trigger with 36" lance.

- **Belt Drive:**

Slower speed increases the life of the pump.

- **High Quality Triplex Plunger Pump:**

All Dynablast pressure washers include GP/Interpump pumps with solid ceramic plungers, thermal pump protector and limited 5 year warranty.

- **Vented Belt Guard:**

Reduces heat and improves belt life

- **Pump Puller:**

Easier belt adjustment



CR4035BGS

SPECIFICATIONS

ASSEMBLED IN CANADA

MODEL	CR4035BG	CR4035BGS
Operating Pressure (PSI):	3500	3500
Volume (GPM):	3.8	3.8
Motor (HP):	13.0	13.0 Electric Start
Pump Speed (RPM):	1450	1450
Dimensions - (LxWxH):	32"x 27"x 25"	32"x 27"x 25"
Unit Weight:	175 lbs	180 lbs

Features and specifications subject to change without prior notice.

Dynablast®



Distributed by:

www.dynablast.com

CRBG 05/12