

DET SERIES

COLD WATER PRESSURE WASHER

Direct Drive • Electric Powered • Industrial Cart

- **Downstream Adjustable Chemical Injector:**
For low pressure soap and chemical injection.
- **Quick Connect Hose Connectors:**
For easy on/off connections and tangle free hoses.
- **Baldor TEFC Motor:**
Low speed induction motor extends the life of your pump.
- **Separate Unloader with Pressure Switch:**
Diverts water pressure when trigger is not in use. Includes easily adjustable pressure control knob and all brass fittings.
- **Inlet Filter:**
Helps reduce contaminants from entering the pump.
- **Time Delay Shutdown:**
Extends the life of your Pressure Washer.

OPTIONAL
HOSE KIT (HR3KIT)
AVAILABLE



C4030DET

- **Heavy Duty Cart:**
Includes gun and lance holder.
With Powder Coated Finish.
- **Four Quick Connect Nozzles:**
Colour coded nozzles included are 0°, 15°, 25° and soap mounted on lance.
- **50' High Pressure Hose:**
Durable non-marking steel braided hose.
- **Quality Gun and Stainless Steel Lance Combination:**
Easy pull trigger with 48" lance.
- **High Quality Triplex Plunger Pump:**
All Dynablast pressure washers include GP/Interpump pumps with solid ceramic plungers, thermal pump protector and limited 5 year warranty.
- **Rubber Foot:**
Reduces vibration.
- **16" Pneumatic Tires**
Ball bearing construction with a steel hub assembly.

Other Features:

- CSA Approved
- Heavy Duty Power Cord and Plug
- Pressure Gauge

SPECIFICATIONS

ASSEMBLED IN CANADA

| MODEL | C4030DET |
|------------------------------|-------------|
| Operating Pressure (PSI): | 3000 |
| Volume (GPM): | 4.0 |
| Motor (HP): | 7.5 |
| Pump Speed (RPM): | 1750 |
| Available Voltage (1 Phase): | 230 |
| Amps: | 33 |
| Wheel Size: | 16" |
| Unit Dimensions (LxWxH): | 41"x31"x24" |
| Unit Weight: | 270 lbs |

Features and specifications subject to change without prior notice.



Distributed by:

Dynablast®



DET.F-06/11

www.dynablast.com