

# DE SERIES

## COLD WATER PRESSURE WASHER

Direct Drive • Electric Powered • Industrial Cart

- **Downstream Adjustable Chemical Injector:**  
For low pressure soap and chemical injection.

- **Quality Gun and Stainless Steel Lance Combination:**  
Easy pull trigger with 48" lance.  
**C2010DEH - 36" Lance**

- **Quick Connect Hose Connectors:**  
For easy on/off connections and tangle free hoses.

- **Baldor TEFC Motor:**  
Low speed induction motor extends the life of your pump.

- **Separate Unloader:**  
Diverts water pressure when trigger is not in use. Includes easily adjustable pressure control knob and all brass fittings.  
**C2010DEH - Built-In Unloader**

- **Inlet Filter:**  
Helps reduce contaminants from entering the pump.

- **Heavy Duty Cart:**  
With powder coated finish.



C4030DEHR  
Shown with  
Optional  
HR3KIT  
Hose Reel

- **Four Quick Connect Nozzles:**  
Colour coded nozzles included are 0°, 15°, 25° and soap mounted on lance.

- **50' High Pressure Hose:**  
Durable non-marking steel braided hose.  
**C2010DEH - 30' Hose**

- **High Quality Triplex Plunger Pump:**  
All Dynablast pressure washers include GP/Interpump pumps with solid ceramic plungers, thermal pump protector and limited 5 year warranty.

- **Rubber Foot:**  
Reduces vibration.

### Other Features:

- Warnock Hersey Certified
- CSA Approved Heavy Duty Power Cord and Plug
- Pressure Gauge

### SPECIFICATIONS

ASSEMBLED IN CANADA

MODEL	C2010DEH	C4030DEHR
Operating Pressure (PSI):	1000	3000
Volume (GPM):	2.1	4.0
Motor (HP):	1.5	7.5
Pump Speed (RPM):	1750	1750
Available Voltage:	115	230
Amps:	14	33
Wheel Size:	Carry Handle	16"
Unit Dimensions (LxWxH):	20"x12"x18"	41"x31"x24"
Unit Weight:	80 lbs	270 lbs

Features and specifications subject to change without prior notice.



C2010DEH



Distributed by:

# Dynablast®



www.dynablast.com

DE-C-02/07