

HOT WATER PRESSURE WASHER

Direct Drive • Electric Powered • Fuel Oil Heated

- Downstream Adjustable Chemical Injector: For low pressure soap and chemical injection.
- Quick Connect Hose Connectors:

For easy on/off connections and tangle free hoses.

- Heavy Duty Steel Frame: Includes protective roll cage, hose holder and a powder coated epoxy finish.
- Large Burner
 Temperature Dial:
 Adjust water temperature
 with ease.
- Easy Access On/Off Toggle Switch: Includes indicator light.
- Replaceable Fuse: For electronic overload protection.
- Easy Access Control Panel: Makes servicing your machine fast and easy.

• Stainless Steel Coil Skin: Durable rust resistant skin. Schedule 80 heating coil and 300,000 BTU burner.



• **13" Pneumatic Tires**: Ball bearing construction with a steel rim and hub assembly.

SPECIFICATIONS	ASSEMBLED IN CANADA	
MODEL	H3025DEF1	H3030DEF1
Operating Pressure (PSI):	2500	3000
Volume (GPM):	3.0	3.0
Motor (HP):	5	6
Available Voltage (1 Phase):	230	230
Amps:	30	30
Pump Speed:	3450	1725
BTU:	300,000	300,000
Time Delay Shutdown:	YES	YES
Unit Dimensions (LxWxH):	42"x28"x43"	42"x28"x43"
Unit Weight:	420 lbs	425 lbs

Features and specifications subject to change without prior notice.





- Four Quick Connect Nozzles: Colour coded nozzles included are 0°, 15°, 25° and soap QC.
- 50' High Pressure Hose: Durable non-marking steel braided hose.
- Quality Gun and Lance Combination: Easy pull trigger with 48" lance.
- Separate Unloader: Diverts water pressure when trigger is not in use. Includes easily adjustable pressure control knob and all brass fittings.
- High Quality Triplex Plunger Pump: All Dynablast pressure washers include GP/Interpump pumps with solid ceramic plungers, thermal pump protector and limited 5 year warranty.
- Large Fuel Oil Tank: Hold up to 4.4 gallons of No.1 or 2 Fuel Oil. Also includes a fuel indicator gauge.

Other Features: •

- High Pressure Blow Off Valve: For added safety.
- Baldor Electric ODP Motor
- Heavy Duty Power Cord
- **12v Beckett Burner:** No external electricity required.



Distributed by: