

# GRGFT SERIES

## SELF CONTAINED MOBILE HOT WATER WASHER

• Gear Reduced • Gasoline Powered • Fuel Oil Heated

- **Stainless Steel Coil Skin:**

Durable rust resistant skin.  
Schedule 80 heating coil  
and 300,000 BTU burner.

- **200 gal water tank:**

Heavy duty polypropylene water  
tank with oversized water outlet  
to feed pump

- **Honda 13HP GX Gasoline Engine:**

Includes electric start  
and low oil alert system.

- **Easy Access On/Off Toggle Switch:**

Includes indicator light.

- **Large Burner**

- **Temperature Dial:**

Adjust water temperature  
with ease.

- **Heavy Duty Steel Frame:**

Includes protective roll  
cage and a powder  
coated finish.

- **Replaceable Fuse:**

For electronic overload  
protection.

- **Hose reels:**

100' water feed hose for tank  
refilling  
100' high pressure hose reel  
accessible with tail gate closed

Hose reels optional.

- **Low speed EVO 3 Interpump**

pump with solid ceramic  
plungers, thermal pump  
protector and limited 5 year  
warranty.

- **Separate Unloader :**

Diverts water back to tank when  
trigger is not in use. Includes  
easily adjustable pressure  
control knob and all brass  
fittings.

- **50' High Pressure Hose:**

Durable steel braided hose.

- **Quick Connect Hose Connectors:**

For easy on/off connections and  
tangle free hoses.

- **Four Quick Connect Nozzles:**

Colour coded nozzles included  
are 0°, 15°, 25° and soap QC.

- **Quality Gun and Lance:**

Combination:  
Easy pull trigger with 48" lance.

- **Downstream Adjustable Chemical Injector:**

For low pressure soap and  
chemical injection.

- **Large Fuel Oil Tank:**

Hold up to 4.4 gallons of No.1  
or 2 Fuel Oil. Also includes a  
fuel indicator gauge.

- **Open Access :**

Open access for battery placement  
burner service within the truck bed.

- **Easy Access Control Panel:**

Access from out side the truck bed  
complete with hour meter. Passenger / curb side  
for added safety.



- **Heavy steel frame with fork lift pockets**

Other Features: ●

- **High Pressure Blow Off Valve:**

For added safety.

- **12v Beckett Burner:**

No external electricity required.

### SPECIFICATIONS

MODEL	H403GRGFT
Operating Pressure (PSI):	3500
Volume (GPM):	3.8
Engine (HP):	13
Pump Speed (rpm) :	1750
Heat input (BTU):	300,000
Burner:	12 Volt
Unit Dimensions (LxWxH):	77"x51x42"
Dry Weight:	836 lbs

Features and specifications subject to change without prior notice.

**Dynablast**<sup>®</sup>  
www.dynablast.com

Designed and  
built in Canada

