

Dynablast[®]

HR3KIT

150 FT Hose Reel Kit Installation Instructions



C4030DEHR Shown with HR3KIT installed



John Brooks Company Limited
2625 Meadowpine Blvd, Mississauga, Ontario L5N 7K5
Ontario/Quebec/Maritimes Tel: 888-881-6667 Fax: 800-350-5666
Alberta/Manitoba/Sask/B.C. Tel: 800-527-8592 Fax: 800-661-3719
www.dynablast.com

Installation instructions

1. Install hose reel into the four holes on nameplate using 5/16 hardware supplied.
2. Apply Teflon tape to the inlet hose on hose reel wrap around eight times.
3. Install 3/8 female NPT fitting into the inlet hose of hose reel.
4. Install 1/4 female JIC fitting end of hose (HW20EXT) into 3/8 female NPT fitting.
5. Remove QC7218 quick coupler from chemical injector.
6. Install 3/8 female BSP 90 degree fitting end of hose (HW20EXT) into the chemical injector.

Bill of Material

Part #	Description	Quantity
HR150	SWIVEL REEL 3000 PSI	1
BOLT5/16X3/4	BOLT 5/16 X 3/4	4
WASHER5/16	5/16 Flat Washer Zinc-plated	4
590-230	WIZ LOCK NUT 5/16	4
TEFLONTAPE	TEFLON TAPE 1/2" X 480" .003	1
HW20EXT	20" HOSE 3/8FNPT JIC x 3/8FBSP 90	1
H5110BAG	2 MIL RECLOSABLE POLY BAG	1

Replacement Parts

Part #	Description
SW13H208	Swivel
HDWARE	Handle
HRRKKIT	Swivel O ring replacement kit