

# HT SERIES

## HOT WATER PRESSURE WASHER

Direct Drive • Electric Powered • Stainless Steel Cart

- **Quick Connect Hose Connectors:**  
For easy on/off connections and tangle free hoses.
- **Baldor Electric TEFC Motor.**
- **Thermally Protected Pump:**  
Up to 190° F.
- **Rubber Foot:**  
Reduces vibration.
- **Flex Coupler:**  
For longer pump and motor life.
- **5 Year Warranty:**  
All Dynablast pressure washers include a 5 year limited warranty.
- **Heavy Duty Stainless Steel Cart:**  
Including Stainless Steel name plate and hose holder.
- **High Pressure Hose:**  
Durable non-marking steel braided hose.  
**C5004HTSS** - 30'  
**C1904HTSS** - 50'  
**C1904HTDS** - 50'  
**C1904HTDS3D** - 50'
- **Quality Gun and Lance Combination:**  
Easy pull trigger with 36" lance.
- **Separate Unloader:**  
Diverts water pressure when trigger is not in use. Includes easily adjustable pressure control knob and all brass fittings.
- **High Quality Interpump HT Series Triplex Plunger Pump:**  
HT Series pumps can run hot water up to 185° F.
- **10" Never-Go-Flat Tires:**  
Ball bearing construction with a steel rim and hub assembly.



### Other Features:

- Brass Y Inlet Strainer
- Gun and Lance Holder

| SPECIFICATIONS               | ASSEMBLED IN CANADA |             |             |                 |
|------------------------------|---------------------|-------------|-------------|-----------------|
|                              | C5004HTSS           | C1904HTSS   | C1904HTDS   | C1904HTDS3D     |
| Operating Pressure (PSI):    | 500                 | 1900        | 1900        | 1900            |
| Volume (GPM):                | 4.0                 | 4.0         | 4.0         | 4.0             |
| Motor (HP):                  | 1.5                 | 5.0         | 5.0         | 5.0             |
| Pump Speed:                  | 1750                | 1750        | 1750        | 1750            |
| Available Voltage (1 Phase): | 115                 | 230         | 230         | 575 V (3-Phase) |
| Amps:                        | 13.5                | 22          | 22          | 5.7             |
| Time Delay Shutdown:         | No                  | No          | Yes         | Yes             |
| Dimensions:                  | 40"x22"x35"         | 40"x22"x35" | 40"x22"x35" | 40"x22"x35"     |
| Unit Weight:                 | 100 lbs             | 195 lbs     | 205 lbs     | 195 lbs         |

Features and specifications subject to change without prior notice.

Distributed by:

# Dynablast®



HT-D-03/10

www.dynablast.com