HVLS1 SERIES

HOT WATER PRESSURE WASHER

Diesel Fired Heater Module

- High Limit Switch:
 For added safety
- Burner Temperature Control:
 Adjust your water temperature with ease.
- High Pressure Blow-Off Valve: For added safety.
- Compact Design: Ideal for tight spaces and stationary applications.
- Cold Water Quick Connect:
 For easy connection to your cold water pressure washer.
- Burner ON/OFF Switch



HV420FLS-12VRED



- Primary Control (CAD):
 On all burners
- Welded 10 Gauge Wrapped Steel Base and Leg Supports
- Stainless Steel Target Plates in all Coils
- Momentary Test, Flow & Thermostat
- Stainless Steel Coil Skin & Rain Cap (300/420 FLS-12V)
- Door with Stainless Steel Hardware (300/420 FLS-12V)
- All Heaters Fuel No. 1 or No. 2
- Powder Coated Paint Finish (Red)



Certified UL1776

ASSEMBLED IN CANADA

SPECIFICATION	NON-STEAM MODELS ETL CERTIFIED			
MODEL	HV300FLS-12VRED	HV300FLS-12V	HV420FLS-12VRED	HV420FLS-12V
Operating Pressure (PSI)	3500	3500	3500	3500
BTU	300,000	300,000	420,000	420,000
Heat Rise	4GPM @ 120°F	4GPM @ 120°F	5GPM @ 120°F	5GPM @ 120°F
Coil	1/2" Schedule 80	1/2" Schedule 80	1/2" Schedule 80	1/2" Schedule 80
Burner	Beckett ADC 12V	Beckett ADC 12V	Beckett ADC 12V	Beckett ADC 12V
Fuel Consumption	1.98 GPH	1.98 GPH	3.06 GPH	3.06 GPH
Coil Water Discharge	Тор	Тор	Тор	Тор
Fuel Pressure Gauge	No	No	No	No
Dimensions (L x W x H)	19" x 19" x 41.75"	19" x 20" x 49.75"	19" x 19" x 51.25"	19" x 20" x 59.25"
weight	340 lbs	345 lbs	375 lbs	380 lbs

Features and specifications subject to change without prior notice.





Distributed by: