

HV SERIES

HOT WATER PRESSURE WASHER

Diesel Fired Heater Module


- **High Limit Switch:**
For added safety
- **Burner Temperature Control:**
Adjust your water temperature with ease.
- **High Pressure Blow-Off Valve:**
For added safety.
- **Compact Design:**
Ideal for tight spaces and stationary applications.
- **Cold Water Quick Connect:**
For easy connection to your cold water pressure washer.
- **Primary Control (CAD):**
On all burners
- **Burner ON/OFF Switch**
- **All Heaters Fuel No. 1 or No. 2**
- **Powder Coated Paint Finish**



HV700F

- **High Pressure & Steam Operating Valves**
- **Welded 7 Gauge Wrapped Steel Base and Leg Supports (700/900).**
- **Welded Inner Coil for Coil Support (700/900)**
- **Stainless Steel Target Plates in all Coils**
- **Momentary Test, Flow & Thermostat**
- **HV120DP, included with HV700F and HV900F**
- **HV12DP, included with HV690F-12V**
- **Removeable Service Access Panel (700/900)**

Access Panel



Certified UL1776
CSA B140-11-M89

ASSEMBLED IN CANADA

SPECIFICATION	STEAM ETL CERTIFIED		
MODEL	HV690F-12V	HV700F	HV900F
Operating Pressure (PSI)	3500	3500	3500
BTU	690,000	700,000	900,000
Heat Rise	7 GPM @ 165°F	7 GPM @ 170°F	10 GPM @ 155°F
Coil	3/4" Schedule 80	3/4" Schedule 80	3/4" Schedule 80
Burner	Beckett SDC 12V	Wayne EH 120V	Beckett CF800 120V
Fuel Consumption	5.06 GPH	5.03 GPH	5.81 GPH
Coil Water Discharge	Bottom	Bottom	Bottom
Dimensions (L x W x H)	26.5" x 26.5" x 58"	26.5" x 26.5" x 58"	26.5" x 26.5" x 64"
weight	790 lbs	790 lbs	1050 lbs

Features and specifications subject to change without prior notice.

Distributed by:

Dynablast®



HV_E - 12/15

www.dynablast.ca