HVLS2 SERIES

HOT WATER PRESSURE WASHER

Diesel Fired Heater Module

- High Limit Switch:
 For added safety
- Burner Temperature Control:
 Adjust your water temperature with ease.
- High Pressure Blow-Off Valve: For added safety.
- Compact Design: Ideal for tight spaces and stationary applications.
- Cold Water Quick Connect:
 For easy connection to your cold water pressure washer.
- Burner ON/OFF Switch



- Primary Control (CAD):
 On all burners
- Welded 7 Gauge Wrapped Steel Base and Leg Supports
- Welded Inner Coil for Coil Support
- Stainless Steel Target Plates in all Coils
- Momentary Test, Flow & Thermostat
- HV120DPLS, included with HV700FLS and HV900FLS
- HV12DPLS, included with HV690FLS-12V
- Removeable Service Access Panel
- All Heaters Fuel No. 1 or No. 2
- Powder Coated Paint Finish

Access Panel





ASSEMBLED IN CANADA

SPECIFICATION	NON-STEAM ETL CERTIFIED		
MODEL	HV690FLS-12V	HV700FLS	HV900FLS
Operating Pressure (PSI)	3500	3500	3500
BTU	690,000	700,000	900,000
Heat Rise	7GPM @ 165°F	7GPM @ 170°F	10GPM @ 155°F
Coil	3/4" Schedule 80	3/4" Schedule 80	3/4" Schedule 80
Burner	Beckett SDC 12V	Wayne EH 120V	Beckett CF800 120V
Fuel Consumption	5.06 GPH	5.03 GPH	5.81 GPH
Coil Water Discharge	Bottom	Bottom	Bottom
Dimensions (L x W x H)	26.5" x 26.5" x 58"	26.5" x 26.5" x 58"	26.5" x 26.5" x 64"
weight	780 lbs	780 lbs	880 lbs

Features and specifications subject to change without prior notice.





Distributed by: