

HVLS1 SERIES

HOT WATER PRESSURE WASHER

Diesel Fired Heater Module

- **High Limit Switch:**
For added safety
- **Burner Temperature Control:**
Adjust your water temperature with ease.
- **High Pressure Blow-Off Valve:**
For added safety.
- **Compact Design:**
Ideal for tight spaces and stationary applications.
- **Cold Water Quick Connect:**
For easy connection to your cold water pressure washer.
- **Burner ON/OFF Switch**



HV420FLS-12VRED



HV300FLS-12V

- **Primary Control (CAD):**
On all burners
- **Welded 10 Gauge Wrapped Steel Base and Leg Supports**
- **Stainless Steel Target Plates in all Coils**
- **Momentary Test, Flow & Thermostat**
- **Stainless Steel Coil Skin & Rain Cap (300/420 FLS-12V)**
- **Door with Stainless Steel Hardware (300/420 FLS-12V)**
- **All Heaters Fuel No. 1 or No. 2**
- **Powder Coated Paint Finish (Red)**



Certified UL1776

ASSEMBLED IN CANADA

| SPECIFICATION | NON-STEAM MODELS ETL CERTIFIED | | | |
|--------------------------|--------------------------------|--------------------|--------------------|--------------------|
| MODEL | HV300FLS-12VRED | HV300FLS-12V | HV420FLS-12VRED | HV420FLS-12V |
| Operating Pressure (PSI) | 3500 | 3500 | 3500 | 3500 |
| BTU | 300,000 | 300,000 | 420,000 | 420,000 |
| Heat Rise | 4GPM @ 120°F | 4GPM @ 120°F | 5GPM @ 120°F | 5GPM @ 120°F |
| Coil | 1/2" Schedule 80 | 1/2" Schedule 80 | 1/2" Schedule 80 | 1/2" Schedule 80 |
| Burner | Beckett ADC 12V | Beckett ADC 12V | Beckett ADC 12V | Beckett ADC 12V |
| Fuel Consumption | 1.98 GPH | 1.98 GPH | 3.06 GPH | 3.06 GPH |
| Coil Water Discharge | Top | Top | Top | Top |
| Fuel Pressure Gauge | No | No | No | No |
| Dimensions (L x W x H) | 19" x 19" x 41.75" | 19" x 20" x 49.75" | 19" x 19" x 51.25" | 19" x 20" x 59.25" |
| weight | 340 lbs | 345 lbs | 375 lbs | 380 lbs |

Features and specifications subject to change without prior notice.

Dynablast®



Distributed by: