

1100

PORTABLE HOSE REELS ON WHEELS

To handle 3/8" through 5/8" I.D. hose.

- Continuous flow reels with swivel joint inlet, fluid hub, outlet riser.
- Comes with cam-lock brake.
- Direct crank rewind.
- One-piece foot, rubber tires and removable steel handlebar.
- Permanently attached crank.
- Standard inlet 90° ball bearing swivel joint 1/2" female NPT threads.
- Standard outlet is 1/2" female NPT threads.
- Pressures to 3000 psi (207 bar).
- Temperatures from +20° F to +400° F (-7° C to +204° C).
- Optional GH Prefix to model # (e.g. GH1100) includes garden hose thread on outlet, stainless steel axle-hub, 5' lead-in hose, and hose end clips.
- Optional pneumatic tires available (prefix model # with AT).
- Stainless steel construction (and internals) available – consult factory.



GH 1100 Configuration Shown

For:

- Grounds Maintenance
- Restaurants/Hotels
- Home Use

Parts Drawing – ISO 48

Model Number	Hose Capacity of Reel				Approx. Weight			Reel Dimensions							
	feet m.				lb. kg.			inches mm.							
	I.D. (in) I.D. (mm)	3/8" 10	1/2" 13	5/8" 16	NET	UPS/ FedEx SHIP Wt.	Frt. SHIP Wt.	A	B	C	D	E	F	G	H
	O.D. (in) O.D. (mm)	3/4" 19	7/8" 22	1" 25											
1100		275 84	175 53	125 38	47 21	100* 45	82 37	21.5 546	12 305	6 152	22 559	16.5 419	24.62 625	39 991	13.81 351

Notes:

1. Specifications subject to change.
2. **Finish:** refer to Page 8.
3. **Be sure to check dimensions and weights prior to ordering.**
* Dimensional weight applies when shipped as a parcel package (via FedEx or UPS Ground).

