

# AT1200

## PORTABLE HOSE REELS ON WHEELS

To handle 1/2" through 1" I.D. hose.



GHAT 1200 Configuration Shown

**For:**

- Grounds Maintenance
- Restaurants/Hotels
- Home Use
- Construction

- Continuous flow reels with swivel joint inlet, fluid hub, outlet riser.
- Standard with cam-lock brake, and pneumatic tires.
- Direct crank rewind.
- One-piece foot, and removable steel handlebar.
- Permanently attached crank.
- Model AT1200 –standard inlet 90° balance pressure swivel joint 1" female NPT threads.
- Standard outlet is 1" female NPT threads.
- Operates at pressures to 1000 psi.
- Temperatures from -40° F to +250° F (-40° C to +121° C).
- Consult factory for other pressures & temps.
- Optional GH Prefix to model # (e.g. GHAT1200) includes garden hose thread on outlet, 5' lead-in hose, hose end clips.
- Stainless steel construction (and internals) available – consult factory.

### Parts Drawing – ISO 87

Model Number	Hose Capacity of Reel					Approx. Weight			Reel Dimensions							
		feet				lb.			inches							
		m.				kg.			mm.							
	I.D. (in) I.D. (mm)	1/2" 13	5/8" 16	3/4" 19	1" 25	NET	UPS/ FedEx SHIP Wt.	Frt. SHIP Wt.	A	B	C	D	E	F	G	H
	O.D. (in) O.D. (mm)	7/8" 22	1" 25	1-9/32" 33	1-9/16" 40											
AT1200		350 107	250 76	150 46	100 30	86 39	147* 67	121 55	24.88 632	11.5 292	8 203	23 584	22.75 578	26.5 673	40 1016	17.25 438

**Notes:**

1. Specifications subject to change.
2. **Finish:** refer to Page 8.
3. **Be sure to check dimensions and weights prior to ordering.**
  - \* Dimensional weight applies when shipped as a parcel package (via FedEx or UPS Ground).

