
# pump repair kits & service accessories



### **RS99 Gear Reducer**



- 5.0 hp Max. Engine Output
- 1450 RPM Pump Speed
- 2.4:1 Reduction Ratio
- 3/4" Diameter Keyed Engine
- Eliminates Belts and Pulleys
- Right or Left Hand Reversible

Mounts to engines with (4) 5/16" threaded holes on 3.62 diameter bolt circle.

See SAE specification J609A for additional information on engine mounting dimensions. Fits Interpump models: T521, 531, 731, 721, 701, 911, 981, 991.

Product No.	Description
RS99	Gear Reducer

### **Aluminum Pulleys**





- 2, 3 and 4-Groove
- 100, 140 & 160 mm Diameter
- 24 or 32 mm Bore

Product No.	Groove	Diameter	Bore
2PY100A24	2	100 mm	24 mm
2PY140A24	2	140 mm	24 mm
2PY160A24	2	160 mm	24 mm
3PY140A24	3	140 mm	24 mm
4PY140B32	4	140 mm	32 mm

### Flex Couplers





Product No.	Shaft Dimension
FC56C2405	24 mm x 5/8"
FC145TC2407	24 mm x 7/8"
FC184TC2409	24 mm x 1-1/8"
FC213215TC2411	24 mm x 1-3/8"
FCL1002408L	24 mm x 1" (for MFG811)

### RS500 & RS500H Gear Reducer



- Gear Reducer for Gas or Diesel Engines
- 3100 RPM Max. Engine Speed
- 25 HP Max. Engine Output
- 1425 RPM Pump Speed
- 1:2.2 Reduction Ration
- Pump Series 47, 47HT, 47SS, 66, 66HT and 66SS

Product No.	Description
RS500*	Gear Reducer
RS500H	Gear Reducer for HONDA Engines
RS5500-28.6	Gear Reducer for 28.6mm shaft
*RS500 Replaces RS151	





- 550 RPM PTO
- 1:1:9 Multiplier
- 1-3/8" Splined Shaft
- Up to 10.0 hp Pumps
- 9.5 lbs Weight

### Fits Interpump models: T-921, T1011B, T1311. T1321, T1511, T1621, T2011

Product No.	Description
MPTO	Gear Multiplier

### **PTO Gear Multiplier**





## **Mounting Flanges**

• Ensure Pump and Motor RPM's Match When Selecting Flanges.

Product No.	HP	Motor Frame
MF56145C	2.0	56C, 145TC, 182C
MF184TC	3.0	184TC
MF213215TC	7.5	213TC, 215TC, 184TC
MFG811B	11.0	Gas Engine

### Maritimes/Quebec/Ontario

www.dynablast.ca

Phone TOLL FREE: 1.800.527.8592 Fax TOLL FREE: 1.800.661.3719