

**HIGH TEMPERATURE UP
TO 185 DEGREES**

HOT WATER



	MPU5004HT	MPU1904HT
Pressure (PSI)	500	1900
Flow (GPM)	4.0	4.0
Motor	1.5 HP TEFC	5 HP TEFC
Motor Speed (RPM)	1750	1750
Power Cord	7 m	7 m
Volts	115 v	230 v
Amps	13.6	23
Pump	Interpump High Temperature Triplex Plunger	Interpump High Temperature Triplex Plunger
Unloader	Separate Adjustable Unloader	Separate Adjustable Unloader
Thermal pump protection	Yes (190 Degrees)	Yes (190 Degrees)
CSA Certified	Yes	Yes
Box Dimensions	28" x 21" x 14"	28" x 21" x 14"
Boxed Unit Weight	75 Lbs	142 Lbs

BALDOR



Distributed by:



	A7500G	A12000G
Pression de la pompe	2500	3000
Débit (gal / min)	3.0	4.0
Moteur	Moteur Honda GX de 6,5 ch avec « Oil Alert »	Moteur Honda GX de 13 ch avec « Oil Alert »
Régime du moteur	3600	3600
Pompe	Triplex Interpump	Triplex Interpump
Injecteur en aval de produits chimiques	Ajustable	Ajustable
Régulateur	Soupape de marche à vide séparée	Soupape de marche à vide séparée
Protection thermique	Oui	Oui
Pistolet	PA RL26	PA RL37
Lance	36"	36"
Boyau haute pression	30 pieds	50 pieds
Buses de lavage	Quatre buses à branchement rapide	Quatre buses à branchement rapide
Construction en acier robuste au fini peint par poudrage	Oui	Oui
Dimensions (Long x larg. x haut.)	33" x 23" x 26"	33" x 23" x 26"
Poids à l'expédition	98 LB	150 LB



Propulsé par
HONDA
MOTEURS



Distribué par: