



fittings components


Stainless Steel Screw Type Quick Couplings



- 3650 psi Max. Pressure
- 10.5 gpm Max. Flow
- 320°F Max. Temperature
- 303 Stainless Steel Construction
- Plastic Anti-Shock Knob
- Viton O-Ring
- Suitable for use in food industry

Product No.	Weight	Size
AR41A	2.3 oz	(Part A) 3/8" BSP-F
AR41B	4.2 oz	(Part B) 3/8" BSP-F


Quick Disconnect Fittings



- 3000 psi Max. Pressure
- 10.5 gpm Max. Flow
- 284°F Max. Temperature
- Screw Type Quick Couplings

Product No.	Connection
QCA250F	1/4" F Plug
QCA250M	1/4" M Plug
QCA375F	3/8" F Plug
QCA375M	3/8" M Plug
QCB250F	1/4" F Coupler
QCB250M	1/4" M Coupler
QCB375F	3/8" F Coupler
QCB375M	3/8" M Coupler
90382000I	O-Ring Replacement
90505200I	Anti-Extrusion Ring


Quick Disconnect Fittings



- 5100 psi Max. Pressure
- 8.0 gpm Max. Flow
- 320°F Max. Temperature
- Screw Type Quick Couplings
- Brass Construction

Product No.	Connection
26063040P	3/8" F Part A
26065050P	3/8" M Part B
10310995P	O-Ring Replacement
10401001P	Anti-Extrusion Ring
10318500P	Large O-Ring Replacement

Quick Disconnect Fittings



- 7250 psi Max. Pressure
- 21.0 gpm Max. Flow
- 320°F Max. Temperature
- Screw Type Quick Couplings
- Stainless Steel Construction

Product No.	Connection
26094070P	1/2" M Part A
26095070P	1/2" F Part B
10311010P	O-Ring Replacement
10401101P	Anti-Extrusion Ring
10318500P	Large O-Ring Replacement

Quick Disconnect Plugs




- Standard O-Rings
- EPR with Teflon coating
- 175°F Max. Temperature

Product No.	PSI	Connection
QC7193	5000	Hardened Steel Brass Plated 1/4" F
QC7194	5000	Hardened Steel Brass Plated 1/4" M
QC7195	4000	Hardened Steel Brass Plated 3/8" F
QC7196	4000	Hardened Steel Brass Plated 3/8" M
PLSS250F	6000	316 Stainless Steel 1/4" F
PLSS250M	6000	316 Stainless Steel 1/4" M
PLSS375F	5000	316 Stainless Steel 3/8" F
PLSS375M	5000	316 Stainless Steel 3/8" M
QC7191	5000	316 Stainless Steel 1/2" F
QC7190	5000	316 Stainless Steel 1/2" M
PLTC250M	5000	1/4" Hardened Stainless Steel
PLTC375M	5000	3/8" Hardened Stainless Steel

Replacement O-Rings

- For Quick Disconnect Fittings

Product No.	Description
QC7109D13	1/4" O-Ring (EPR)
QC7109D14	3/8" O-Ring (EPR)
QC7109D37	1/2" O-Ring (EPR)
QC7109D26	1/4" O-Ring (Viton)
QC7109D40	3/8" O-Ring (Viton)
QC7109D42	1/2" O-Ring (Viton)



Quick Disconnect Sockets



- Standard O-Rings
- EPR with Teflon coating
- 175°F Max. Temperature

Product No.	PSI	Connection
QC7214	5000	Brass 1/4" F
QC7210	5000	Brass 1/4" M
QC7218	4000	Brass 3/8" F
QC7217	4000	Brass 3/8" M
QC7235	2200	Brass 1/2" F
QC7230	2200	Brass 1/2" M
QDSS250F	6000	316 Stainless Steel 1/4" F
QDSS250M	6000	316 Stainless Steel 1/4" M
QDSS375F	5000	316 Stainless Steel 3/8" F
QDSS375M	5000	316 Stainless Steel 3/8" M
QDSS500F	5000	316 Stainless Steel 1/2" F
QDSS500M	5000	316 Stainless Steel 1/2" M


Easy Grip Quick Connects



- Brass

Product No.	Pressure	Description
EGQC250F	5000 PSI	QC 1/4" x 1/4" NPT-F
EGQC250M	5000 PSI	QC 1/4" x 1/4" NPT-M
EGQC375F	4000 PSI	QC 3/8" x 3/8" NPT-F
EGQC375M	4000 PSI	QC 3/8" x 3/8" NPT-M

PA Quick Couplers



- 3650 psi Max. Pressure
- 10.5 gpm Max. Flow
- 320°F Max. Temperature
- Brass

Product No.	Description
AR1BM375	3/8" NPT-M Coupler, part B
AR1BF375	3/8" NPT-F Coupler, part B
AR1AM375	3/8" NPT-M Coupler, part A
AR1AF375	3/8" NPT-F Coupler, part A
AR1BM250	1/4" NPT-M Coupler, part B
AR1BF250	1/4" NPT-F Coupler, part B
AR1AM250	1/4" NPT-M Coupler, part A
AR1AF250	1/4" NPT -F Coupler, part A

Inlet Fittings



Product No.	Description
SGF0004BR	Brass 1/2" F Inlet
SGM0004BR	Brass 3/8" M Inlet
D10010	Garden Hose Assembly (3/4" M Inlet, 1/2" QD-M Outlet)
D10011	Plug (3/4" M Inlet, 1/2" QD-M Outlet)
D10012	Coupler (3/4" M Inlet, 1/2" QD-M Outlet)
GP680073	Garden Hose Inlet (3/4" Garden Hose x 1/2" BSP-M)

NEW!

GPD10119 Manifold Block



- 4000 psi Max. Pressure
- 3 Way
- Bolt Down

Product No.	Description
D10119	3/8" NPT-F

**Looking to Buy Volume?
Call Us for Case Lot Pricing.**



fittings components

Series "A" - Male Adapter/Female Thread



Product No.	Connection
AGGLP100A	1" Male Adapter x FPT
AGGLP125A	1-1/4" Male Adapter x FPT
AGGLP150A	1-1/2" Male Adapter x FPT
AGGLP200A	2" Male Adapter x FPT
AGGLP300A	3" Adapter x FPT

Series "D" - Female Lever Coupler/ Female Thread



Product No.	Connection
AGGLP100DNL	1" Female Coupler x FPT
AGGLP125DNL	1-1/4" Female Coupler x FPT
AGGLP150DNL	1-1/2" Female Coupler x FPT
AGGLP200DNL	2" Female Coupler x FPT
AGGLP300DNL	3" Female Coupler x FPT

Series "B" - Female Lever Coupler / Male Thread



Product No.	Connection
AGGLP100BNL	1" Female Coupler x MPT
AGGLP125BNL	1-1/4" Female Coupler x MPT
AGGLP150BNL	1-1/2" Female Coupler x MPT
AGGLP200BNL	2" Female Coupler x MPT
AGGLP300BNL	3" Female Coupler x MPT

Series "E" - Male Adapter/Hose Shank



Product No.	Connection
AGGLP100E	1 Male Adapter/Hose Shank
AGGLP125E	1-1/4 Male Adapter/Hose Shank
AGGLP150E	1-1/2 Male Adapter/Hose Shank
AGGLP200E	2" Male Adapter/Hose Shank
AGGLP300E	3" Male Adapter/Hose Shank

Series "C" - Female Lever Coupler / Hose Shank



Product No.	Connection
AGGLP100CNL	1" Female Coupler x Hose Shank
AGGLP125CNL	1-1/4" Female Coupler x Hose Shank
AGGLP150CNL	1-1/2" Female Coupler x Hose Shank
AGGLP200CNL	2" Female Coupler x Hose Shank
AGGLP300CNL	3" Female Coupler x Hose Shank

Series "F" - Male Adapter/Male Thread



Product No.	Connection
AGGLP100F	3/4 Male Adapter x MPT
AGGLP125F	1-1/4 Male Adapter x MPT
AGGLP150F	1-1/2 Male Adapter x MPT
AGGLP200F	2" Male Adapter x MPT
AGGLP300F	3" Male Adapter x MPT

Maritimes/Quebec/Ontario

Phone TOLL FREE: 1.888.881.6667
Fax TOLL FREE: 1.800.350.5666

A20

www.dynablast.ca

Alberta/Manitoba/Sask/BC

Phone TOLL FREE: 1.800.527.8592
Fax TOLL FREE: 1.800.661.3719

components fittings



John Guest Fittings

Super Speedfit fittings & shut-off valves require no tools. Simply insert tubing into the fitting/shut-off valve collet to ensure a secure connection. Whether you are using plastic or soft metal tubing, the integrity of the connection.

- 33°F Min. Temperature
- Available in 1/8" to 3/8" Size Configurations
- Made of all FDA approved materials
- NSF Certified

Fittings

- 150 psi Rated Pressure at 70°F
- 100 psi Rated Pressure at 150°F

Shut-Off Valves

- 150 psi Rated Pressure at 70°F
- 60 psi Rated Pressure at 140°F

All John Guest fittings are sold in packages of 10 fittings.

Male Connector



Product No.	Connection Type
PI010821S	1/4" x 1/8" NPT-M
PI010822S	1/4" x 1/4" NPT-M
PI010823S	1/4" x 3/8" NPT-M
PI011221S	3/8" x 1/8" NPT-M
PI011222S	3/8" x 1/4" NPT-M
PI011223S	3/8" x 3/8" NPT-M
PI011224S	3/8" x 1/2" NPT-M
PI011623S	1/2" x 3/8" NPT-M
PI011624S	1/2" x 1/2" NPT-M

Female Adaptor



Product No.	Connection Type
PI450822S	1/4" x 1/4" NPT-F
PI451222S	3/8" x 1/4" NPT-F

Bulkhead Union



Product No.	Connection Type
PI1208S	1/4" to 1/4"
PI1212S	3/8" to 3/8"
PI1216S	1/2" to 1/2"

Union Tee



Product No.	Connection Size
PI0206S	3/16"
PI0208S	1/4"
PI0212S	3/8"
PI0216S	1/2"

Union Elbow



Product No.	Connection Size
PI0306S	3/16"
PI0308S	1/4"
PI0312S	3/8"
PI0316S	1/2"

Union Connector



Product No.	Connection Size
PI0406S	3/16"
PI0408S	1/4"
PI0412S	3/8"
PI0416S	1/2"

Maritimes/Quebec/Ontario

Phone TOLL FREE: 1.888.881.6667
Fax TOLL FREE: 1.800.350.5666

A21

www.dynablast.ca

Alberta/Manitoba/Sask/BC

Phone TOLL FREE: 1.800.527.8592
Fax TOLL FREE: 1.800.661.3719



fittings components

Swivel Elbow



Product No.	Connection Type
PI090821S	1/4" x 1/8" NPT-F
PI090822S	1/4" x 1/4" NPT-F
PI091221S	3/8" x 1/8" NPT-F
PI091222S	3/8" x 1/4" NPT-F
PI091223S	3/8" x 3/8" NPT-F
PI091622S	1/2" x 1/4" NPT-F
PI091623S	1/2" x 3/8" NPT-F
PI091624S	1/2" x 1/2" NPT-F

Swivel Branch Tee



Product No.	Connection Type
PI100821S	1/4" x 1/8" NPT-F
PI100822S	1/4" x 1/4" NPT-F
PI101222S	3/8" x 1/4" NPT-F
PI101223S	3/8" x 3/8" NPT-F
PI101623S	1/2" x 3/8" NPT-F
PI101624S	1/2" x 1/2" NPT-F

Stem Adaptor



Product No.	Connection Type
PI050821S	1/4" x 1/8" NPT-F
PI050822S	1/4" x 1/4" NPT-F
PI050823S	1/4" x 3/8" NPT-F
PI051222S	3/8" x 1/4" NPT-F
PI051223S	3/8" x 3/8" NPT-F
PI051623S	1/2" x 3/8" NPT-F
PI051624S	1/2" x 1/2" NPT-F

Cross Connector



Product No.	Connection Size
PI4712S	3/8" Cross

Fixed Elbow



Product No.	Connection Type
PI480821S	1/4" x 1/8" NPT-F
PI480822S	1/4" x 1/4" NPT-F
PI480823S	1/4" x 3/8" NPT-F
PI481222S	3/8" x 1/4" NPT-F
PI481223S	3/8" x 3/8" NPT-F

Reducing Branch Tee



Product No.	Connection Type
PI301208S	3/8" - 1/4" - 3/8"
PI301612S	1/2" - 3/8" - 1/2"

End Stop



Product No.	Connection Size
PI4608S	1/4"
PI4612S	3/8"

Shut-Off Valve



Product No.	Valve Type	Connection Type
PPSV010822W	Straight Valve	1/4" x 1/4" NPT-F
PPSV011223W	Straight Valve	3/8" x 3/8" NPT-F
PPSV040808W	Straight Valve	1/4" - 1/4"
PPSV041212W	Straight Valve	3/8" - 3/8"
PPSV500822W	NPT-F Elbow Valve	1/4" x 1/4" Female
PPSV501222W	NPT-F Elbow Valve	3/8" x 1/4" Female

Maritimes/Quebec/Ontario

Phone TOLL FREE: 1.888.881.6667
Fax TOLL FREE: 1.800.350.5666

A22

www.dynablast.ca

Alberta/Manitoba/Sask/BC

Phone TOLL FREE: 1.800.527.8592
Fax TOLL FREE: 1.800.661.3719

components fittings



Tools



Other sizes and configurations are available. Please contact John Brooks Customer Service for a complete catalogue.

Product No.	Description
TSNIP	Tube Cutter
TSPITool	1/4" - 3/8" Release Tool Set

Tube Support



Product No.	Connection Type
TSI250S	5/16" - 1/4"
TSI312S	3/8" - 5/16"
TSI375S	1/2" - 3/8"

Tube to Hose



Product No.	Connection Type
PI250808S	1/4" - 1/4"
PI251208S	3/8" - 1/4"
PI251212S	3/8" - 3/8"
PI251212SL	3/8" - 3/8" (Long)
PI251216S	3/8" - 1/2"
PI251612S	1/2" - 3/8"
PI251616S	1/2" - 1/2"
PI290808S	1/4" - 1/4"
PI291208S	3/8" - 1/4"

Locking Clips



Product No.	Description
PIC1808R	1/4" Locking Clip
PIC1812R	3/8" Locking Clip

Maritimes/Quebec/Ontario

Phone TOLL FREE: 1.888.881.6667
Fax TOLL FREE: 1.800.350.5666

A23

www.dynablast.ca

Alberta/Manitoba/Sask/BC

Phone TOLL FREE: 1.800.527.8592
Fax TOLL FREE: 1.800.661.3719