



**FILTRI
FILTERS**

■ **F10**

Alluminio
Aluminium

200/310 microns



10 bar
1 MPa
145 psi
100 l/min
26.4 gpm

■ **F30**

Polipropilene
Polypropilene

170/365 microns



8 bar
0,8 MPa
120 psi
230 l/min
61 gpm

**VALVOLE DI MASSIMA PRESSIONE
MAX PRESSURE SETTING VALVES**

■ **S723**

Ottone
Brass



700 bar
70 MPa
10150 psi
230 l/min
60.8 gpm

■ **SX2**

Acciaio inox
Stainless steel



720 bar
72 MPa
10442 psi
190 l/min
50 gpm

**REGOLATORI DI PRESSIONE
REGULATING VALVES**

■ **R1**

Ottone
Brass



R1/200 - R1X/200
200 bar
20 MPa
2900 psi
110 l/min
29 gpm

R1/400 - R1X/400
400 bar
40 MPa
5800 psi
110 l/min
29 gpm

■ **R1X**

Acciaio inox
Stainless steel



R1/600 - R1X/600
600 bar
60 MPa
8700 psi
70 l/min
18.5 gpm

**VALVOLE AUTOMATICHE
UNLOADER VALVES**

■ **RA2**

210 bar
21 MPa
3045 psi
230 l/min
61 gpm

Ottone
Brass



■ **BH210**



■ **RA2L**

210 bar
21 MPa
3045 psi
230 l/min
61 gpm

Ottone / Con
leva di bypass
Brass / With
bypass level



210 bar
21 MPa
3045 psi
10-110 l/min
2.6-29 gpm

Max.
Temperature
85 °C (185°F)

**VALVOLE PNEUMATICHE
PNEUMATICALLY OPERATED VALVES**

■ **PN2**

Acciaio inox
Stainless steel



■ **PN2/140**

140 bar
14 MPa
2030 psi
230 l/min
61 gpm

■ **PN2/250**

250 bar
25 MPa
3626 psi
230 l/min
61 gpm

■ **PN2/500**

500 bar
50 MPa
7250 psi
230 l/min
61 gpm

**LANCE COMPLETE
SPRAY GUNS**

■ **P560**

Lunghezza 750/1000mm
Lenght 750/1000mm



600 bar - 60 MPa - 8700 psi
60 l/min - 15.8 gpm

■ **P560/S**

Lunghezza 750/1000mm
Lenght 750/1000mm



600 bar - 60 MPa - 8700 psi
60 l/min - 15.8 gpm

UGELLI / NOZZLES

■ **N1**

Acciaio inox
Stainless steel



Max. 300 bar
Max. 30 MPa
Max. 4350 psi

**ACCUMULATORI ANTIPULSAZIONI
PULSATION DAMPENERS**

■ **A4X**

Volume 0,35 l
Volume 0,35 l

Acciaio inox
Stainless steel



Max. 210 bar
Max. 21 MPa
Max. 3045 psi

**MANOMETRI
PRESSURE GAUGES**

■ **PG1** ■ **PG2**



0-120 bar 0-12 MPa
0-160 bar 0-16 MPa
0-250 bar 0-25 MPa
0-400 bar 0-40 MPa
0-600 bar 0-60 MPa
0-1000 bar 0-100 MPa

Attacco Gas 1/4"
Connection Gas 1/4"

**VALVOLE NON RITORNO
CHECK VALVES**

■ **UD1**

Pre carica / Load
5 bar - 0,5 MPa - 72 psi
0,2 bar - 0,02 MPa - 3 psi



UD1/5
UD1/02
250 bar
25 MPa
3650 psi
180 l/min
48 gpm

**SLITTE TENDICINGHIE
SLIDES**

■ **TC-G**



Per installazioni fino a 50 hp/37 kW
For installation up to 50 hp/37 kW